

Technical Data Sheet CB9193

DESCRIPTION

CB9193 can be used as universal masterbatch for Polycarbonate, Pentaerythritol tetrastearate, Nylon and other carrier resin that commonly have the property of the high melting point. Since carbon content is 50 percent, it is possible to present a high blackness even with less input of masterbatch.

KEY FEATURES

PETS carrier
Good dispersion

High Content of Jet carbon black
Easy control processing

APPLICATIONS

Compound

COMPATIBILITY

PE, ABS, PBT, PC, PA

GOOD

TYPICAL PROPERTIES

Base resin		Pentaerythritol tetrastearate	
Carbon black content		50%	
Carbon black diameter		18nm	
Appearance		Pellet	
Melt index flow	ASTM D1238	237.42 g/10min	300 °C / 10kg

 The data in the table above are typical test values intended as only guidance.

PACKAGING

PP Laminated Paper Bag - 25kg

Packing method requested by the clients may add an extra charge.

Muil Chemical Co., Ltd.

Headquater 237, Yeosusandan-ro, Yeosu-si, Jeollanam-do, Korea

Seoul office #1103, Dae-o Bldg., 53-1, Yeouinaru-ro, Yeongdeungpo-gu, Seoul, Korea

Tel +82-61-690-9411

Fax+82-61-685-4332

Home page : www.muilchemical.com

ver.2 20180504